

Haki dwurożne uniwersalne

Nr art.: DD2661



Udźwig dla grupy natężenia pracy mechanizmu dźwigniicy wg PN-79/M-06504					l ₁	*) l ₂ min	*) l ₃ min	Gwint d		a ₁	a ₂	d ₁	d ₃	f
1M 2M	3M	4M	5M	6M				metryczny wg PN-83/M-02013	trapezowy zaokrąglony wg PN-83/M-84550					
t					mm									
	0,8	0,63	0,5	0,4	25	25	90	M 16	-	34	27	24	12	13
0,6	1,25	1	0,8	0,63	30	31	95	M 20	-	38	30	26	16	15
	1,6	1,25	1	0,8	30	31	105	M 24	-	40	32	32	20	16
0,2	2,5	2	1,6	1,25	35	37	115	M 30	-	45	35	36	25	18
	4	3,2	2,5	2	40	46	125	M 36	-	50	40	42	30	22
	6,3	5	4	3,2	45	52	145	M 42	-	56	45	48	35	23
0	8	6,3	5	4	50	65	160	M 48	-	63	50	56	40	26
2,5	10	8	6,3	5	56	70	195	M 56	-	71	56	63	48	30
6	12,5	10	8	6,3	58	72	215	M 60	-	80	63	70	52	33
0	16	12,5	10	8	62	80	245	M 64	-	90	71	75	55	37
5	20	16	12,5	10	68	95	265	M 72	-	100	80	85	63	42
2	25	20	16	12,5	80	100	290	-	Tr Z 80x10	112	90	95	68	47
0	32	25	20	16	90	110	325	-	Tr Z 90x12	125	100	106	75	53
0	40	32	25	20	100	120	365	-	Tr Z 100x12	140	112	115	85	60
3	50	40	32	25	110	135	410	-	Tr Z 110x12	160	125	132	95	67
0	63	50	40	32	125	150	445	-	Tr Z 130x14	180	140	150	110	75
00	80	63	50	40	135	160	510	-	Tr Z 140x14	200	160	170	120	83
25	100	80	63	50	150	185	570	-	Tr Z 160x16	224	180	190	140	95